

Z-SS1010R

Speaker Selector



Speaker Selectors

TOA speaker selector Z-SS1010R is a 10 zone BGM or 10 zone paging speaker selector. This highly efficient speaker selector can be installed with the public address system in schools, malls, offices, and places requiring the selection of speakers.

Features:

- DC 24 V operation
- LED indicator for each selector
- 1U 19" rack size

- 10 selectors for paging & background music
- Protection against DC input overload and reversed DC polarity installation



Product Specifications

	Z-S\$1010R
Voltage Source	24V DC
Current Consumption	0.4A DC
Input	10 Input BGM/Paging, 1 Link as Input/Output
Output	10 Output with 3 wire R-H-C each output max 480W
Controls	Front: 10 BGM selectors, 1 all call selector for all paging Rear: 1-10 paging controls In, all paging control in for all paging
Indicator Led	10 BGM Selector LEDs, 10 Paging Selector LEDs, 1 All Call LED
Operating Temperature	0°C to + 40°C
Finish	Front Panel : Aluminum Hair Line, Etching Black ; Case: Steel Plate, Painting Black
Dimensions	420(W) x 44(H) x 320(D) in mm
Weight	3.2kg
Accessories	6P Connector (12pcs), 2P Connector (1pcs)



