



ZS-BM800-AS

SPEAKER SYSTEM



Harmonious **design**, exceptional **sound**

Enhanced Safety and Ease in Installation

This smart feature frees up both hands for wiring and precise angle adjustments, eliminating the need to support the speaker's weight. More efficient installation process that significantly reduces the risk of accidents or equipment damage.



Temporary Docking

Hands-Free Operation

Wiring with Both Hands

ZS-BM800-AS



- Versatile 8-inch 2-way surface-mount speaker system
- Perfect for music and announcements
- Sleek design for seamless integration with walls and ceilings
- Safe and easy installations with included mounting bracket
- Temporary docking feature allows effortless wiring and positioning
- Flexible angle adjustment for both wall and ceiling mounts
- Ideal for permanent installs or portable setups

Specifications

ZS-BM800-AS

Enclosure	Bass-reflex type
Rated Input	60 W (100 V line)
Rated Impedance	100 V line: 170 Ω (60 W), 330 Ω (30 W), 670 Ω (15 W), 3.3 kΩ (3 W)
Sensitivity	91 dB (1 W, 1 m) at installation in 1/2 free sound field
Frequency Response	70 Hz - 20 kHz, -10 dB at installation in 1/2 free sound field
Crossover Frequency	3 kHz
Directivity Angle	Horizontal: 100°, Vertical: 100°
Speaker Component	Low frequency: 20 cm (8") PPcone-type High frequency: 25 mm (1") dome tweeter
Input Terminal	Push-in terminal
Operating Temperature	-10 °C to +50 °C (14 °F to 122 °F)
Installation Environment	Indoor installation
Finish	Enclosure: HIPS, black Grille: Steel plate, black (RAL 9011 equivalent), paint Speaker bracket: Die-cast aluminum, black (RAL 9011 equivalent), paint Base bracket: Steel plate, t.4.5, black (RAL 9011 equivalent), paint Base bracket cover: HIPS, black (RAL 9011 equivalent), paint
Dimensions	251 (W) X 392 (H) X 216 (D) mm (9.88" X 15.43" X 8.5")
Weight	5.2 kg (11.46 lb)
Accessory	Speaker bracket ...1, Base bracket ...1, Base bracket cover ...1, Bracket fixing screw ...1 set
Option	Adapter plate: HY-F08B Speaker stand: ST-34B Note: K&M 19780 or K&M 19610 is required.

Note: Bolts and nuts for mounting the bracket to the wall or ceiling are not included. Prepare them separately.

Optional Accessories

The HY-F08B adapter plate is necessary for mounting the speakers on a stand.



HY-F08B



Application Example : House of Worships



Scan for more info