

# HORN SPEAKER

## DESCRIPTION

The ZH-5025B is designed to be used exclusively in the paging or intercom system. To avoid the unit's failure, do not sound a signal tone from this speaker for long time.

## SPECIFICATIONS

|                                |  |  |
|--------------------------------|--|--|
| Model                          | ZH-5025B                                     |  |
| Input                          | Rated 25W                                    |  |
| Impedance                      | 16Ω  |  |
| Sound Pressure Level (Average) | 110dB (1W, 1M) at (Hz) 500, 1000, 1500, 2000 |  |
| Frequency response (Hz)        | 200 ~ 6,000                                  |  |
| Ambient Temperature            | -20°C to +55°C                               |  |
| Finish                         |  |  |
|                                | 1 HORN-A                                     | Aluminium, off white                       |
|                                | 2 REFLECTOR HORN                             | ABS resin, off white                       |
|                                | 3 BRACKET                                    | Steel, off white                           |
|                                | 4 BRACKET HOLDER                             | ADC, off white                             |
|                                | 5 REAR COVER                                 | ABS resin, grey                            |
|                                | SCREW & BOLT                                 | Steel, electro plating (chromate)          |
|                                | SPEAKER CABLE                                | Polyvinyl chloride insulated cabtyre cable |
| Weight                         | 4.4kg  |  |

## APPEARANCE

