


DESCRIPTION

The Z-HA1060-AS is composed of multiple horn speakers positioned in an array. It is a highly efficient speaker. Clear voice can be transmitted to a distant place without acoustic correction. The built-in high-pass filter cuts the bass that can damage the speaker. A double drip-proof structure, and a salt-resistant paint finish, it has excellent durability in an outdoor permanent environment.

SPECIFICATIONS

Rated Input	60 W
Rated Impedance	100 V line: 170 Ω (60 W), 330 Ω (30 W) 70 V line: 83 Ω (60 W), 170 Ω (30 W)
Sensitivity	111 dB (1 W, 1 m) (500 Hz – 5 kHz, IEC60268-5)
Max. SPL	128 dB (60 W, 1 m) (500 Hz – 5 kHz, IEC60268-5)
Frequency Response	520 Hz – 4.6 kHz (–10 dB) 350 Hz – 11 kHz (–20 dB)
Speakers Component	Horn speaker unit $\times$ 8
Operating Temperature	–20 $^{\circ}$ C to +55 $^{\circ}$ C (–4 $^{\circ}$ F to 131 $^{\circ}$ F)
Dust/Water Protection	IP66
Connection	Speaker Cable (4-core cabtyre cord 2 m (6.56 ft))
Finish	Case: Aluminum, white (RAL 9016 equivalent), paint Front grille: Aluminum, white (RAL 9016 equivalent), paint Bolts: Stainless steel
Dimensions	167 (W) $\times$ 1233 (H) $\times$ 140.5 (D) mm (6.57" $\times$ 48.54" $\times$ 5.53") (excluding projection)
Weight	14 kg (30.86 lb) (unit only)
Option	Speaker mounting bracket: YS-1100A

APPEARANCE



UNIT:mm SCALE:1/15

Note: Numerical values in parentheses are for reference only.