

DESCRIPTION


The PA Amplifier ZA-230W, designed to fulfill requirement arrange voice like paging, oration, ceremony, inter communication, religious service place, car- calling, and others.

SPECIFICATIONS

\* 0 dB = 1 V

Power Source	220 V AC, or 12 V DC
Rated Output	30 W
Power Consumption	34 W (AC operation at IEC60065)
Current Consumption	4.5 A (DC operation at rated output)
Frequency Response	50 Hz - 20 kHz, ±3 dB
Distortion	1 % or less at 1 kHz, 1/3 rated power
Input	MIC 1 - 3: -60 dB* (1.0 mV), 600 Ω, unbalanced, phone jack AUX: -24 dB* (60 mV), 10 kΩ, unbalanced, RCA pin jack
Output	Speaker out: Floating balanced High impedance: 330 Ω (100 V) Low impedance: 4 Ω (11 V)
S/N Ratio	60 dB or more (MIC 1 - 3) 70 dB or more (AUX)
Tone Control	Bass: -10 dB at 100 Hz Treble: -10 dB at 10 kHz
Indicator	Power LED, Signal LED
Finish	Panel: ABS resin, black Case: Steel plate, black
Dimensions	350 (W) x 100 (H) x 240 (D) mm (13.78" x 3.94" x 9.45")
Weight	3.5 kg (7.72 lb)

APPEARANCE



UNIT:mm SCALE:1/3