

WIRELESS MEETING AMPLIFIER ZW-G10CB-AS

■ DESCRIPTION

The ZW-G10CB-AS is a wireless meeting amplifier that has an elegant design and durable. It offers reliable performance, clear, powerful sound, can accept up to two microphone wireless and is simple to operate.

■ SPECIFICATIONS

* 0 dB = 1 V

-31 LOTI TOATTONS			
Power Source	AC In: 220 - 240V, 50/60 Hz;		
	DC In : 12V 1A, Max. 18V;		
	DC: 12V/2.3Ah (Rechargeable Battery)		
Power Consumption	AC : 20W, 0.1A (at Rated Output);		
· · · · · · · · · · · · · · · · · · ·	DC : 30W, 1.6A (at Output Power Max)		
Output Power	20W Max.		
Frequency Response	60 Hz - 20 kHz, ±3dB		
Distortion	Less Than 5%		
	Mic 1 & 2 : -40 dB* Unbalanced 5k Ω , 2Pole—Phone Jack;		
Inputs	Aux In : $-20dB*$ Unbalanced 10k Ω , RCA Pin Jack		
0.45.45	Aux III ZOUDE UNDUIGNEEU TUKSZ, NOA FIII JUCK		
Outputs	Audio Out: -25dB* Unbalanced 40kΩ, RCA Pin Jack;		
	Speaker Out: 8 - 16Ω, RCA Pin Jack		
sources	Handheld Microphone, Frequency Range 180 — 200MHz; RF Power Output <10mW;		
	Body Pack microphone (can be used with Tieclip Mic or Headset Mic),		
	Frequency Range 180 - 200MHz, RF Power Output <10mW;		
	USB Player (support up to 32GB), recording function,		
	Type of File (MP3 file and Wav file);		
	SD/MMC Card Player (support up to 32GB), recording function,		
	Type of File (MP3 file and Wav file);		
	Type of File (MP3 file and Wav file); Bluetooth Connection, Class 2, Freq.: 2400 - 2483.5 MHz, Ch: 0 - 78,		
	Max. RF Transmit Power +4dBm;		
	Cassette Player, recording function;		
	FM Radio (88 – 108 MHz)		
Controls	2 Microphone Gain Controls;		
001111013	1 Aux Gain Controls;		
	1 MP3 Gain Controls;		
	1 Echo Controls;		
	1 Tone Controls;		
To die of our	1 Power ON/OFF Switch		
Indicators	1 LED Display;		
	1 LED Charge;		
	1 LED Bat Low;		
	1 LED Power;		
	1 LED RF1;		
	1 LED RF2;		
	1 LED Rec (for Usb/SD Card);		
	1 LED Record Cassette		
Battery Live	Approx. 5 Hours, Continuous Music		
Charging Time	12 hours, 12V/2.3Ah, Lead Acid Battery, 1 pcs		
S/N Ratio	60 dB or more		
Antenna	Rod antenna		
Speaker	6 " Cone (150mm), 4 Ω , Full Range		
Operating Temperature			
Finish	Plastic resin, light gray		
Dimensions	234 (W) × 341 (H) × 180 (D) mm, (9.21"× 13.42"× 7.08")		
Weight	3.8 Kg (8.37 lb)		
Accessory	Dower cord (1.5m)1;		
ACCESSOI Y	Remote Control and inside the battery type CR 2025 3V1;		
	Handheld Wireless Mic:-:1;		
	Body Pack Wireless Mic···1;		
	Headset Mic-1;		
	Tieclip Mic···1		

Notes: o The design and specifications are subject to change without notice for improvement. o Specifications are measured on 220V AC. o Frequency Available are applied to each product as follows:

	No	Frequency	Guidance colors
Г	1	181.60 MHz	Green
		199.75 MHz	Orange
Г	2	182.40 MHz	Blue
		190.60 MHz	Yellow
Γ	3		Dark Yellow
		192.60 MHz	Red

Page 1/2

DWG No: 506416001 Rev. 01