

■DESCRIPTION

The ZS-HS1500PW is a 2-way speaker system with digital Amplifier made of resin, and features a large diameter woofer. It can be installed and used in many different application with combined use of the supplied accessories and/or the optional mounting brackets.

■SPECIFICATIONS

Enclosure	Sealed type
Power Source	220 - 240 V AC (50/60Hz)
Rated Output	170W
Power Consumption	100W
Sensitivity	98 dB (1W, 1m)
Frequency Response	60Hz - 20kHz
Input	MIC/LINE : XLR-3-31 type combination connector (balanced/unbalanced, -60dB/0dB selective) AUX : XLR-3-31 type connector, -10dB unbalanced
Output	LINE out : XLR-3-31 type connector, 0dB unbalanced
Tone Control	Bass : ±10dB at 100Hz Treble : ±10dB at 10kHz
Operating Temperature	-10°C to 40°C
Finish	Enclosure : Polypropylene, white Punched net : Surface-treated steel plate white
Dimension	451 (W) X 560 (H) X 400 (D) mm (17.76" X 22.04" X 15.75")
Weight	16kg (35.2 lb) unit only
Accessory	Power cord (2m)×1
Option	Mounting Bracket :HY-1500VW, HY-1500HW ; Ceiling mount bracket :HY-C0801 Wall mount bracket : HY-W0801 ; Speaker stand: ST-34B

■APPEARANCE

