

## DESCRIPTION

The Z-5BW-HX2 is a 2-way compact speaker system that permits both constant directivity control over a wide frequency range and changes in directivity. It is ideal for reproducing clear sound in with long reverberation times or high background noises. It is designed for outdoor use.

## SPECIFICATIONS

Enclosure	Sealed type
Power Handling Capacity	Continuous: 200 W, Program: 400 W (IEC 60268-5)
Rated Impedance	8 Ω
Sensitivity (1 W, 1 m)	96 dB (60° mode), 97 dB (45° mode), 98 dB (30° mode), 99 dB (15° mode) *
Frequency Response	95 Hz - 20 kHz (-10 dB) (60° mode), 100 Hz - 20 kHz (-10 dB) (45° mode), 105 Hz - 20 kHz (-10 dB) (30° mode), 110 Hz - 20 kHz (-10 dB) (15° mode)
Crossover Frequency	4 kHz
Directivity Angle	Horizontal: 100° (2 kHz or more) Vertical: 60° (800 Hz or more), 45° (1.2 kHz or more), 30° (1.6 kHz or more), 15° (3.2 kHz or more) variable
Speaker Component	Low frequency: 12 cm cone-type x 4, High frequency: Balanced dome-type x 12
Speaker Cord	2-core cabtyre cord with diameter of 6 mm
Water Protection	IPX4 (Install with the every speaker module downward.)
Operating Temperature	-15 °C to +50 °C
Finish	Enclosure: Polypropylene, black Punched net: Surface-treated steel plate, black, rust proof coating
Dimensions	408 (W) x 546 (H) x 342 (D) mm
Weight	16 kg
Accessory	Hanging bracket x2, Hex. wrench x1
Option	Matching transformer: MT-200 Speaker mounting bracket: ZY-PF1WP, ZY-CW1WP, ZY-WM1WP, ZY-WM2WP, ZY-CN1B-WP

## APPEARANCE

\*(Factory-preset: 60° mode)

