

DESCRIPTION

The Z-5WW-HX2 is a 2-way compact speaker system that permits both constant directivity control over a wide frequency range and changes in directivity. It is ideal for reproducing clear sound in spaces with long reverberation times or high background noises. It is designed for outdoor use.

SPECIFICATIONS

Enclosure	Sealed type
Power Handling Capacity	Continuous: 200 W, Program: 400 W (IEC 60268-5)
Rated Impedance	8 Ω
Sensitivity (1 W, 1 m)	96 dB (60° mode), 97 dB (45° mode), 98 dB (30° mode), 99 dB (15° mode) *
Frequency Response	95 Hz - 20 kHz (-10 dB) (60° mode), 100 Hz - 20 kHz (-10 dB) (45° mode), 105 Hz - 20 kHz (-10 dB) (30° mode), 110 Hz - 20 kHz (-10 dB) (15° mode)
Crossover Frequency	4 kHz
Directivity Angle	Horizontal: 100° (2 kHz or more) Vertical: 60° (800 Hz or more), 45° (1.2 kHz or more), 30° (1.6 kHz or more), 15° (3.2 kHz or more) variable
Speaker Component	Low frequency: 12 cm cone-type x 4, High frequency: Balanced dome-type x 12
Speaker Cord	2-core cabtyre cord with diameter of 6 mm
Water Protection	IPX4 (Install with the every speaker module downward.)
Operating Temperature	-15 °C to +50 °C
Finish	Enclosure: Polypropylene, white Punched net: Surface-treated steel plate, white, rust proof coating
Dimensions	408 (W) x 546 (H) x 342 (D) mm
Weight	16 kg
Accessory	Hanging bracket x2, Hex. wrench x1
Option	Matching transformer: MT-200 Speaker mounting bracket: ZY-PF1WP, ZY-CW1WP, ZY-WM1WP, ZY-WM2WP, ZY-CN1W-WP

APPEARANCE

* (Factory-preset: 60° mode)

