



offers reliable performance, clear and powerfull sound

# PORTABLE AMPLIFIER **ZW-S110SD-AS**



TOA Indonesia

# ZW-S110SD-AS

## SPECIFICATIONS

Speaker	6ohm / 1" tweeter, 4ohm/10" woofer
Receiver Module	UHF PLL Non-diversity receiver module ( 2 pc receivers) with 16 user selectable channels (UHF 655-681 Mhz)
Output Power	70W (RMS)/ 100 W (MAX) (Class- D Amplifier)
Frequency Response	70Hz ~ 15KHz (+ 3dB)
Function	CD Player, USB (support up to 32GB); SD / MMC Card (support up to 32 GB); Mic Input x 2 (phone jack x 1, combination XLR & phone jack x 1); Line Input (RCA x 1 or phone jack x 1) Mixed Out x 1 (phone jack); External speaker out x 1 (Phone Jack) ; Tuner Unit x 2 (WTU-Z100)
Charging Time	12V/5Ah (2pcs) Lead Acid battery : 6-8 hours 1.2V/1.3Ah Nickel-Metal Hybride battery : 5 hours (for microphone)
Operating Time	Averagely 3-9 hours (depending on volume)
Power Supply	100-240V (90-264V) switching power supply
Rechargeable Battery	12V/5Ah Lead Acid battery : 2 pcs 1.2V/1.3 Nickel - Metal Hybride battery : 4 pcs (for microphone)
Frame Material	Plastic-steel material with water resistance; Panel : Plastic with painting Black, Grille : Metal with painting black
Dimensions	560(H) x 330(W) x 310(D)mm
Weight	16.5 kg (without Microphone)
Accessories	Remote control x 1, AC power cord x 1 (Type C), Hex head wrench x 1, Blank cover x 2, Handheld microphone x 1, Lavalier microphone x 1
Options	Speaker stand : ST-34B

### Notes

\* Specifications are measured on 220V AC

\* The design and specifications are subject to change without notice for improvement

