



ZS-FB2862C-AS

Ceiling Subwoofer



Smiles
for the
Public

Low frequency range
& high-quality sound output


ZS-FB2862C-AS Ceiling Subwoofer

TOA's ceiling subwoofer ZS-FB2862C-AS offers an attractive exterior design created by an interior designer to blend it naturally to any architectural space, enhancing the immediate area's sense of harmony. The bass reflex speaker system designed to provide low frequency range and high-quality sound output, ideal for locations with high ceiling or places that requires true-to-life sounds. The ZS-FB2862C-AS permits versatile mounting to match a wide range of applications and installation locations with the use of its optional mounting hardware.

Key Features:

- 16 cm cone-type, 60W continuous
- Tapping switch allows for 70V/100V or 8Ω operation
- Rotating grille for quick & convenient installation
- Low pass filter with overload protection

Installation Example



Specifications

Model	ZS-FB2862C-AS
Rated Input	120W (High Impedance)
Power Handling Capacity	Continuous: 60W (8Ω) (IEC60268-5), Program: 120W (8Ω)
Rated Impedance	100V line: 83Ω (120W), 170Ω (60W), 330Ω (30W), 670Ω (15W), 3.3kΩ (3W), 8Ω (120W)
Sound Pressure Level	87dB (1W,1m) installation in ½ free sound field (Measured by installing the unit in the center of a ceiling or wall) 81dB (1W,1m) installation in free sound field (Measured in anechoic chamber)
Frequency Response	60-250Hz (-10dB) Installation in ½ free sound field (Measured by installing the unit in the center of a ceiling or wall)
Speaker Component	Low frequency: 16 cm cone-type
Mounting Hole	φ 250mm (Maximum ceiling thickness: 37mm)
Input Terminal	Removable locking connector with screw-down terminals (2 input terminals & 2 bridge terminals)
Usable Cable	Solid copper wire: φ0.5 – φ1.6mm (equivalent to AWG No. 24-14) Stranded copper wire: 0.2 - 2.5mm ² (equivalent to AWG No. 24-14)
Finish	Enclosure: Steel plate, plating, Baffle: Fire-resistant ABS resin (UL-94 V-0), black, Rim: Fire-resistant ABS resin (UL-94- V-0), white (RAL 9016), Punched net: Steel plate, white (RAL 9016) paint
Dimensions	φ280 x 198 (D) mm (φ11" x 7.79")
Weight	6.3kg (including mounting accessory)
Accessory	Grille x 1, Ceiling reinforcement x 1, Safety wire x 1, Paper pattern x 1
Option	Anchor hanging bracket: HY-AH1, Tile Bar Bridge: HY-TB1



TOA Indonesia

TOA
Smiles for the Public

www.toa.co.id

Specifications are subject to change without notice.