



ZS-760B-AS / ZS-760W-AS

2-Way Weatherproof Loudspeaker System



Bringing you
high sound quality
under all weather conditions.

The horn speaker that fits all your need for **excellent speech** and **BGM clarity** in the open...



ZS-760B-AS / ZS-760W-AS 2-Way Weatherproof Loudspeaker System

- Highly intelligible: suited to voice alarm, public address and BGM application by 2-way speaker system.
- IP66 certified: All weather durability, be it water or dust. Ideal for any fully outdoor applications.
- Special paint coat prevents color degradation, ensuring long-lasting exterior condition.
- Rotary switch facilitates hassle-free impedance change.
- Various mounting brackets available as accessories allowing flexibility of mounting the speaker on a platform, in the ceiling, on the wall or on a pole.

APPLICATION EXAMPLES



Parking spaces



Railway stations



Amusement parks



Sports fields

SPECIFICATIONS

	ZS-760B-AS	ZS-760W-AS
Rated Input		60 W (high impedance)
Rated Impedance		100V Line: 170 Ω (60W), 330 Ω (30W), 670 Ω (15W), 1.3kΩ (7.5W) 70V Line: 83 Ω (60 W), 170 Ω (30 W), 330 Ω (15 W), 670 Ω (7.5W)
Sensitivity (1 W, 1 m)		100 dB
Maximum SPL (60W, 1 m)		117 dB
Frequency Response		100Hz - 20 kHz
Crossover Frequency		2.5 kHz
Directivity Angle		Horizontal: 90°; Vertical : 80°
Speaker Component		Low Frequency: 16 cm (6") cone-type High Frequency: 2.5 cm (1") dome tweeter
Dust/Water Protection		IP66
Connection		Speaker cord (Hot: Black; Corn: White)
Finish	Enclosure: ABS, Black, Paint Coating Punched Net: Surface-treated Steel Plate, Black, Paint Coating Bracket: Stainless Steel, Black, Powder Coating	Enclosure: ABS, White, Paint Coating Punched Net: Surface-treated Steel Plate, White, Paint Coating Bracket: Stainless Steel, White, Powder Coating
Dimensions		388(W) x 310(H) x 367(D)mm
Weight		7.4kg

