

■DESCRIPTION

The ZH-P620S-AS is a highly intelligible speaker with a built-in 20W digital power amplifier, that provides public address announcement and remote paging via network video surveillance applications. Its powder-coated finish and stainless steel screws ensure the unit's weatherproof capability.

■SPECIFICATIONS

0 dB = 1V

Power Source	12V-24VDC, 1.5A-2A ( DC Socket "+" Type A : 5.5 x 2.1mm )
Power Consumption	15W (1.25A) at Rated output 25W (2.10A) at Maximum output
Input	0 dB*, 10kΩ, Unbalanced (RCA plug)
Signal Gain	8, 16, 24 or 32db (Factory pre-set to 16db)
Volume Adjustment	Internal volume control (Factory pre-set to maximum position)
Sound Pressure Level	113dB (1W, 1m at 500Hz to 2.5KHz peak level) Max. SPL (above 120dB)
Frequency Response	250 - 10,000 Hz
Operating Temperature	-20°C to +55°C (must be free from dew condensation)
Dust/Water Protection	IP 65
Finish	Horn Flare: HIPS resin, white (RAL9010 equivalent) Reflector horn and case: ABS resin, white (RAL9010 equivalent) Bracket, screws & bolts: Stainless steel
Cable Cord	Length: 2m Flying Lead (RCA plug) & DC socket ("+" )
Dimesions	292 (W) x 230 (H) x 280 (D) mm
Weight	Approx. 1.8 kg
Option	Z-AD2430-AS AC/DC Adaptor

Notes: The design and specifications are subject to change without prior notice for improvement.

■APPEARANCE

